

FLOORING SURFACES QUIETSTEP

For Architects,
Specifiers and
General Contractors

Special Features

- Resilient flooring
- Ideal ballet floor
- Reduces sound
- Life expectancy: up to 18 years
- Guarantee: 7 years against wear

Portable or permanent resilient flooring for studio, stage and touring. Provides additional cushioned response for wood subflooring and reduces sound. Provides additional insulation for a warmer floor surface. Surface can also be treated for differing degrees of non-slip. Use with floating wood subfloor or on stage.

ACTIVITY


Quietstep is ideal for ballet, pointe and aerobics over sprung subfloor system.

INSTALLATION

Quietstep can be installed directly on a floating wood subfloor or hard wood surface, temporarily, semi-permanently, or permanently using double-faced tape, adhesive or Re-Use-It.

MAINTENANCE

Clean weekly, using Proclean, a detergent/ degreaser that does not leave a residue.




Quietstep

Colors available for immediate shipment



Quietstep Custom Colors Available

Allow 6 weeks for delivery



See reverse side for flooring specifications and MSDS Ratings.

STAGESTEP

Flooring Systems for Dance, Theatre and the Performing Arts.

800-523-0960 (Toll free in the U.S. & Canada) • 215-636-9000

www.stagestep.com • stagestep@stagestep.com



FLOORING SURFACES QUIETSTEP

TYPE

Hardwearing vinyl floorcovering with a closed cell PVC foam backing.

COLORS

1 standard solid color
13 special order color available

THICKNESS

.126"
(3.2 mm)

WIDTH & LENGTH

6.56' x 65' = 426.4 ft²
2 lm x 20 lm = 40 lm²

WEIGHT

6 lbs. per sq. yd.
3.25 kg per sq. meter

QUALITY STANDARDS

Quietstep is manufactured to meet all the performance requirements of the following standards:

Europe: EN 651: 1996
Use area classification: EN 685: 34/42

FIRE RATINGS

prEN 13501-1 - Class Cfl-S1

SLIP RESISTANCE

Class DS

SOUND REDUCTION

Quietstep
ISO 717-2 19dB +/- 2

DIMENSIONAL STABILITY

Dimensional Stability EN 434 +/- 0.2% max
Residual Indentation 0.4 mm
Castor Chair No visible
Abrasion Resistance EN660-1 T
Color Fastness ISO 105-B02 >=6

For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Stagestep.

Information on this specification sheet supercedes all materials published prior to April 2011.

STAGESTEP

Flooring Systems for Dance, Theatre and the Performing Arts.

800-523-0960 (Toll free in the U.S. & Canada) • 215-636-9000

www.stagestep.com • stagestep@stagestep.com