

Super Bravo B/C

- Hardwearing, heterogenous reversible sheet flooring
- Colors - Black/Black, Grey/Grey, Black/White, and Black/Grey

SPECIFICATION



1.7mm
.06 in



N/A



N/A



2m x up to 30m
6.56ft x up to 98ft



2.17kg/m2
4lbs/yd2

SUPER BRAVO B/C

HETEROGENOUS



GENERAL PERFORMANCE

EN 651



ACOUSTIC IMPACT SOUND REDUCTION

ISO 717-2 10dB



SLIP RESISTANCE

AS/NZS 4856 R9
DIN 51130 R9



REACTION TO FIRE

EN 13501-1 Class Cfl-s1
DIN 4102/ONORM = B1
ASTM E662 < 450
ASTM E648 Class 1



RESISTANCE TO CHEMICALS

EN 423 (ASTM F 1303-99)
Excellent chemical resistance



LIGHT FASTNESS

EN 20105-B02 (Method 3) ≥6



ABRASION RESISTANCE

EN 649 Group T



INDENTATION - RESIDUAL

EN 433 <0.2mm



DIMENSIONAL STABILITY

EN 434 0.2



FLEXIBILITY

EN 435 (Method A) Pass



VOC EMISSIONS

No Solvents Used



THERMAL CONDUCTIVITY

N/A



HYGIENE

Contains antimicrobial agents for improved hygiene protection. This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection.



ELECTRICAL BEHAVIOUR (body voltage)

EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'.



APPLICATIONS

Ballot, Modern, Jazz, Call for percussive use



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, call 800-523-0960



PERFORMANCE AND PROPERTIES